




MATERIAL

INSULATOR: NY-66 GLASS-REINFORCED THERMOPLASTIC.
CONTACT: BRASS.
PLATING: MATING AREA - GOLD FLASH GOLD OVER NICKEL.
SOLDER AREA - TIN OVER NICKEL.

ELECTRICAL


VOLTAGE RATING: 250 VAC RMS.
CURRENT RATING: 1 AMP.
DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC RMS 60Hz
FOR 1 MINUTE.
INSULATION RESISTANCE: 1000 MEGOHMS MIN AT 500 VDC.
CONTACT RESISTANCE: 30 MILLIOHMS MAX.

MECHANICAL




RETENTION FORCE: 460 GRAMS MIN PER CONTACT.
INSERTION FORCE: 230 GRAMS MAX PER CONTACT PAIR.
WITHDRAWAL FORCE: 15 GRAMS MIN PER CONTACT PAIR.

ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C.



SECTION A-A



RECOMMENDED PCB LAYOUT (TOP VIEW)

Circuit	Dimension			Circuit	Dimension		
	A	B	C		A	B	C
04	8.64	3.81	1.27	38	30.23	25.40	22.86
06	9.91	5.08	2.54	40	31.50	26.67	24.13
08	11.18	6.35	3.81	42	32.77	27.94	25.40
10	12.45	7.62	5.08	44	34.04	29.21	26.67
12	13.72	8.89	6.35	46	35.31	30.48	27.94
14	14.99	10.16	7.62	48	36.58	31.75	29.21
16	16.26	11.43	8.89	50	37.85	33.02	30.48
18	17.53	12.70	10.16	52	39.12	34.29	31.75
20	18.80	13.97	11.43	54	40.39	35.56	33.02
22	20.07	15.24	12.70	56	41.66	36.83	34.29
24	21.34	16.51	13.97	60	44.20	39.37	36.83
26	22.61	17.78	15.24	80	56.90	52.07	49.53
28	23.88	19.05	16.51	128	87.38	82.55	80.01
30	25.15	20.32	17.78	132	89.92	85.09	82.55
32	26.42	21.59	19.05				
34	27.69	22.86	20.32				
36	28.96	24.13	21.59				

			 www.bessure.com Mob:+86 136 3177 3595		品號 PART NO.		CS12L-XXXX		日期 DATA		2013/03/29	
					圖號 DRAWING NO.		CS12L-XXXX		繪圖 DRAWN		Sayid	
					客戶品號 CUSTOMER P/N				核對 APPROVED		Max	
REV.	DESCRIPTION	DATA	TITLE: 1.27mm pitch Card Edge Dip Post			REV. A	公差 TOLERANCE	.X ±0.25 .XX ±0.20	比例 SCALE	FREE	單位 UNIT	mm